

Linx 4900

Cleaner. Clearer. Cleverer.



Cleaner.

- Stainless steel cover has no dirt traps and provides a surface off which liquid naturally slides.
- IP55 rating - the new enclosure design is ideal for washdown environments such as food packaging, without the added cost of factory air.
- Autoflush of the printer and conduit at shutdown ensures that the printer is always ready for a trouble-free start up.
- Ink and solvent refilling is mistake proof and mess free.

Clearer.

- Printhead is designed specifically for two-line printing and uses an intelligent jet control system for maintaining print quality.
- Printhead temperature, time of flight and ink pressure are all managed by the printer itself for trouble-free viscosity control and consistent print quality, with no need for manual intervention.
- Sealed printhead incorporates a valve system for clearer, cleaner start-ups, even after extended shutdowns.
- Clear, simple user interface with WYSIWYG message display means that messages are created, selected, edited and printed right first time.

Cleverer.

- The Linx 4900 is cleverly designed to ensure minimal intervention is needed from the user.
- Running parameters are monitored and adjusted by the printer itself, with clear on-screen diagnostics.
- The user never needs to open the enclosure, thus reducing potential damage to critical components.
- No manual adjustments are needed to the printhead.
- Up to 50 messages can be stored, and selected via a preview screen for easy identification.
- When printing is finished, a simple one-button press will shut down the printer and switch it off.

The Linx 4900

Dimensions (mm)



*Including clearance

Performance

Printhead	ULTIMA 1 or 2	ULTIMA plus 1 or 2
Lines of print supported	2.1 to 7.7mm	2.6 to 8.8mm
Character height range	6.25 m/s	7.28m/s
Maximum speed: single line print, wide pitch	2222	2133
Maximum number of characters per second	✓	✓
Standard speed (SS) print option	Optional	Optional
High speed (HS) print option	Optional	Optional
Super high speed (SHS) print option	Optional	Optional
Maximum message length (number of characters)	682	682
Graphics/logo printing	✓	✓
Number of message types	Up to 9	Up to 9

General features

Single button startup and shutdown	✓
Menu-driven message creation and editing	✓
Integral QWERTY keypad (full size)	✓
WYSIWYG message display	✓
High brightness back-lit LCD display with adjustable contrast (black on white, 256x64 pixels)	✓
Mistake proof mess free ink and solvent refilling	✓
Auto printhead and conduit flush	✓
Auto power off	✓
Choice of operator languages	21
Printer status indicators (4 LEDs)	✓
Full on-screen diagnostics	✓
Password protected functions	✓

Programming and printing facilities

Fixed and variable text	✓
Upper-case and lower-case characters	✓
Bold factor up to 9 times	✓
Character height, width and delay functions	✓
Automatic formats for shift coding, dates and times	✓
Flexible date and time format options	✓
Real-time clock functions	✓
Automatic date forward function	✓
Batch coding and counting	✓
Sequential numbering	✓
Reverse printing	✓
Timed-message function	✓
LogoJet® PC-based message and logo creation software	Optional
DDE Driver for PC application development	Optional

Memory capacity

Message storage capacity (number of messages)	Up to 50
Logo storage capacity on PROM (number of logos)	Up to 100

Printhead options

Ultima (62µm)	✓
Ultima plus (75µm)	✓
90° printhead configuration	Optional
2m conduit	✓
4m conduit	Optional
Positive air purge to printhead	Optional
Cutaway printhead cover tube	Optional
Magnetic shielded cover tube	Optional

Ink range

Linx MEK base (dye/pigmented excluding white)	✓
Linx mixed base	✓
Linx ethanol base	✓

Connections/interfacing for

Shaft encoder	✓
Product detector	✓
External single stage alarm output	✓
RS232	✓
Volt-free contact alarm connection	Optional
LogoJet® and DDE Driver software	Optional

Physical characteristics

Stainless steel base and cover	✓
Environmental protection rating (EN60529:1991 / IEC60529:1989)	IP55
Mounting options	Bench or console
Operating temperature range	5 – 45°C
Humidity range (relative humidity, non-condensing)	10 – 90%
Power supply	100 – 230V 50/60Hz
Power rating	200W
Weight	20kg

Regulatory approvals

TÜV/GS	✓
CE mark	✓
FCC	✓



THINKING ALONG YOUR LINES

For more information, contact
Linx Printing Technologies plc,
Burrell Road, St Ives,
Cambridgeshire PE27 3LA, UK.
Telephone +44 (0)1480 302100
Fax +44 (0)1480 302116
email sales@linx.co.uk

www.linx.co.uk